



Context-Aware Personalization Architectures for Intelligent Recommendations and Digital Service Optimization

Dr Somasundaram Krishnan

Principal and Professor of Computer Science and Engineering, Sri Muthukumaran Institute of Technology,
Chennai, India

ABSTRACT: A personalization that is situation-dependent has become a central feature of smart-recommender systems and optimization of content, service and interactions in digital media whereby platforms can customize the content, service and interactions to the different needs of the user and the dynamic environment. Nonetheless, the older models of personalisation normally work opposing a pre-established pattern or signal of behaviour and therefore, cannot comprehend and perceive the temporal, contextual and cross domain purpose the user. The scenario that the paper suggests is a Context-Aware Personalization Framework (CAPF) that incorporates the user profiles, past behavioral history, present contextual signals, semantic preference model and adaptive recommendation systems into a unified framework. The framework involves context acquisition layer where the multimodal signals are gathered, context modeling layer where dynamically changing user-context representations are generated and the intelligent recommendation layer which is a combination of machine learning, deep learning and contextual ranking. An optimization layer that operates on a feedback loop evaluates user reactions, and update personalization policies, a privacy and governance layer makes sure that they handle the data responsibly. The suggested structure gives the power of changes in real time, explainable recommendations, service optimizations and personalization of services which evolves in real time within the online platform. The architecture provides a scalable foundation to applications like e-commerce, online health care, e-learning, smart services and personalized content delivery.

KEYWORDS: Context-Aware Personalization, Intelligent Recommendations, User Modeling, Contextual Computing, Adaptive Services, Machine Learning, Digital Service Optimization.

I. INTRODUCTION

The rapid expansion rate of digital platforms has ever-changed the way users access information, products, services as well as interactive applications. The current generation of systems like e-commerce systems, online health software, online learning systems, and streaming applications and smart-service platforms produce vast levels of behavioral and contextual data. In such conditions it is less and less possible to provide the same content or service to all the users. The user varies in terms of tastes, resolution and intention, model of behavior, time requirements as well as contextual requirements. The intelligent personalization, therefore, has been one of the crucial features to provide pertinent recommendations and optimize digital services in the light of personal needs and circumstances.

The main form of data upon which traditional recommender systems rely is the historical interactions, user ratings or the similarity of the items. These methods may be helpful in providing valuable suggestions, and may not work well in bringing out the dynamic nature of the user preferences. The interest of the user may change depending on the time, place and number, depending on the recent activities and the immediate intention as well as depending on the previous activity and focus. Research over time-conscious recommendations has unveiled the significance of identifying the long-term interest and short-time behavioral patterns [1]. On the same note, dynamical intent model and preference evolution approaches show signs of the past behavior not showing real needs of the user rather than the current needs [3], [4]. Such constraints are what drive the creation of personalization architectures which could be constantly improved with additional, but ever changing contextual information.

Machine learning, deep learning, sequential modeling, representation learning, and reinforcement learning have greatly increased the functions of recommendation systems with artificial intelligence. Recommendation methods that are AI based can understand the relationships between complicated behavioral patterns and find patterns that are hard to model using more traditional rule-based methods [2]. The top models have also covered more the dual-view preference



learning [5], and dynamic and static representation learning [6] as well as the joint modeling of long/short-term interests [7]. These methods enhance the better results on the recommendations and obtains more enriched users and items representation. However, the majority of the existing solutions continue to be based on prioritizing recommendations rather than personalizing as a problem of digital optimization of services.

Personalization is further enhanced introducing context-driven, which considers a user context he or she has been involved with a digital service. Environmental indicators can be time, place, device features, condition of the environment, tracks, and trails, history of communication with the partner, and intent. By combining these signals; the systems will be in a position to acquire knowledge to differentiate between the stable preferences and pressing needs. Further, the personalization may be further developed with textual and visual features, semantic features, such as keywords and other heterogeneous features [8], [9] and [11]. These skills are especially relevant in contemporary online setting where top-notch integrated sources are required to provide relevant personalization, other than a single sign of behavior.

Another very important need is constant accommodation. Reactions of users to recommendations give an important feedback that could be utilized in improving the following decisions. The interactive feedback has been demonstrated to be helpful with adaptive personalization through recommendation secured through reinforcement-learning [10]. An intelligent system can perform an intelligent bypass of the one time prediction task of recommendation and dynamically evaluate user responses and revise its personalization policy as more and more information comes in. Meanwhile, each of the individualization architectures has to take care of the privacy, scalability and responsible data management. A case study of federated recommendation algorithms indicates the possibility that one can determine individualized models without extensive use of a centralized repository of user-data collection [12]. Consequently, a sensible personalization architecture would be defined as an architecture that might balance between personalization intelligence, capacitance, explicability and scaling performance and privacy.

However, despite such significant advancements, the existing literature typically refers to such abilities in various contexts and to separate models or solution-specific to regions. Various aspects that are commonly carried out are: Temporal recommendation, intent recognition, preference learning, multimodal representation, the process of feedback optimization and privacy-conscious learning. This fragmentation restricts potential of digital platforms to offer comprehensive, persistently adaptive personalization.

To address this deficiency, this paper proposes a Context-Aware Personalization Framework (CAPF) to smart suggestions and increase of digital services. One architecture comprises of the context acquisition, dynamic user modeling, semantic preference representation, adaptive recommendation, feedback-driven optimization and privacy and governance. CAPF perceives process of personalization as an end to end process where contextual cues are received, user representation is kept updated and recommendations are made based on the prevailing circumstances and system behaviour is improved by giving feedback. The proposed architecture offers an intelligent, scalable backbone of knowledge personalisation of e-commerce, healthcare, learning, intelligent services and intelligent content environments, and enables it to provide smarter, more explainable and responsible digital-service delivery.

II. RELATED WORK

Recent studies of intelligent recommender systems have been moving towards the latter (dynamic, contextual and adaptive personalization) as opposed to the former (user profiling fixed). This change is particularly acute concerning digital services, the tastes of which, their inclinations, and circumstances under which they can change all the time. Sequential behaviour, intent recognition, preference dynamics, explainability, reinforcement learning and privacy conscious recommendation have been studied in the literature with regard to modeling temporal models. Such capabilities are created independently and not as a part of one and the same personalization architecture.

The time-intelligent recommendation is also a significant starting point to the moving user interests modeling. Zhang et al. immersed a time aware long- and short-term attention system called TLSAN that reflect long-term and short-term interest of the user to suggest the next item [1]. The approach will benefit the complementary recommendation models by establishing the various temporal preference patterns, and hence enhancing the reactionary behavior of the recommendation models towards different user behavior. Context-driven personalization heavily depends on this time modeling because the user prefers can not always be considered to be fixed. Bheemisetty has released the review till the AI-based recommendation systems with focusing on the recent AI method, personalization, and feasible implementation of recommendations [2]. The article belongs to the broader movement to recommend solutions that are



smarter but the article could have been expanded to include the greater breadth of opportunities in terms of architecturally integrating contextual cues, feedback and governance.

Dynamic intent modeling would be the other direction that could help. Zhang et al. recommended that dynamic intent could avail offered iterative denoising network session based recommendation [3]. Strategy will focus on identifying the dynamism of the user intents in the session and discarding frail and wasteful information about behavior slicing. This becomes even more so when considering systems based on the context since the intent instant may be enormous in terms of a historical user profile. Pujahari et al. tackled preference evolution time dependent Markov random fields, i.e. they model explicitly the time dependent evolution of user preferences [4]. Their work describes how the shift in the temporal preferences can come to their rescue in the personalization and what is it that makes the dynamic representation of the user necessary (compared to the fixed profile).

The issue of adaptive preference learning has been a burning point, as well. To obtain adaptive recommendation when the aspects of the preferences of users that are complementary should be captured to enhance the quality of the recommendation, Liu et al. proposed dual-view preference learning [5]. The exploration unveils the necessity of being educated in different attitudes of user behavior that can be generalised into the integration of historical, contextual, semantic and real time references. Liu et al. also investigated the dynamic and the static representation learning of the recommendation [6]. Their choice considers a fact that the recommendation models are to remain comparatively constant in the user properties but simultaneously they need to be in a position to follow dynamically changing user interests. This postulate is nearly parallel to the suggested framework which separates the persistent user profiles and the constantly changing contexts representations.

It is especially crucial when the long- and short-term interests are integrated in the domain of optimization of digital services. Xiao et al. developed a new system of e-commerce joint learning recommendation where both the long run and short-term interests of the users are taken into consideration [7]. Through their work, it is shown that an integration of various dimensions of temporal preference can enhance service delivery which is personal to individuals. However, recommendation models that focus on e-commerce tend to put performance ranking at focus, whilst personalization of digital services in general needs extra features, and capabilities that include contextual adaptation of a service, optimization of service, feedback processing and governance.

Explainability and multimodal information is another important aspect of personalization. Another approach to explainable recommendation is a dynamic attention-based one that Liu has presented along with others that take into account the features of both text and the image [8]. The dissimilar data to be unified lets offers better user and item representations and offers explainable recommendations. Likewise, Gu et al. proposed an amalgamation of feature fusion sequence neural network to make recommendations [9]. Formation of multi-feature integration shows significance of merging different levels of behavior and item cues instead of concealing on one communication. All these studies support the emphasis of the proposed architecture in combining semantic and contextual features.

Adaptive interaction has also been dealt with through reinforcement learning in order to adapt to the feedback. An interactive, food recommender system navigated by Liu et al. is a type of recommendation system based on reinforcement learning, meaning that it can be improved with each revision of the user [10]. The comparison between a learning structure that uses keywords enriched with the travel recommendation designed by Chen et al showed that semantic keywords can be useful as far as learning more discriminative representations of preferences is concerned [11]. The implication of these two studies is that personalization might be advanced with a continual communication and semantic comprehension, however, these two studies have specific focus areas of application.

Finally, privacy, scalability and distributed data processing should also be a target of personalization. Imran et al. postulated ReFRS a resource efficient federated recommender system which has the capability to cater to diversified and dynamic preferences of the users [12]. The idea of federated recommendation is a great guideline towards privacy conscious personalization systems since it minimizes reliance on single point user-data collection. The privacy aware learning, in-turn, is not equipped to offer an integrated service optimization architecture.

III. CONTEXT FUSION AND ADAPTIVE PERSONALIZATION INTELLIGENCE ARCHITECTURE

The proposed Context-Aware personalization Framework (CAPF) is proposed as a transformation end-to-end architecture of heterogeneous user, behavioral, contextual and environmental cues, to flexible recommendation and optimal digital services. This contrasts with the traditional recommender systems which is primarily a preference



prediction or item ranking system and CAPF views personalization as a continuous intelligence process, which involves a context acquisition, user-state formation, semantic meaning, recommendation generation, feedback analysis and governance. The architecture will be designed in such a way that it will provide a list of interconnected layers that will guarantee that any new requirements of the user can be captured and mapped on service options on a near real time basis.




Figure 1 – Overall CAPF Architecture

3.1 Context Signal Acquisition Layer

CAPF lowest layer handles the acquisition of the signals that one must understand what the user being served is about. The signals are acquired on various sources such as the profile of the user, a track of interaction, browsing, transactions, the history of search, session, device, times place and environment. Implicit feedbacks that consist of the number of clicks, time in looking, navigation behaviour, purchase history and frequency of interaction are summed up with explicit inputs that are ratings, preferences, queries, chosen categories.

Signal checks, signal normalisation and time stamping and rejection of noise as information is followed by the acquisition layer before data is sent to later layers. This is necessary since raw behavioral data might have incomplete, redundant or inconsistent observations. Time signals are particularly considered to be useful as interests, which are expressed by the user, may contain fixed and rapidly changing elements [1], [4]. The layer thus retains the historical as well as the interaction streams over the last few times to facilitate dynamic personalization.

3.2 Dynamic Context Modeling Layer

The second level transforms the heterogeneous messages into coded meanings of the current context of the user. CAPF is dynamically user experience related to attributes which are fairly fixed, and dynamically operational attributes. The fixed qualities are mainly the not yet developed preferences, the existing interests and are dynamic current session intent, present-temporal conditions and instant behavior change.

This separation will enable the structure to have a long-term individualization without historical action taking over the present will. This is especially often in the area of dynamic intent modeling insofar as what the user viewed as objective might be viewed as different to what the user views as objective historically [3]. Similarly the active and passive learning of the representations demonstrate the value of retaining the persistent and the evolving representation qualities of the users [6]. CAPF thus nibbles on the dynamic context image each time they have seen some important new signals.

3.3 Semantic Preference and Representation Layer

The third layer transforms context/behavioural information to high level preference representations. It integrates user properties, item properties, semantic keywords, text, visual properties and easy sequence properties, to yield more interesting user interest properties. The inclusion of diverse features may enhance the quality of suggestions through the



assistance of supplementary sources of information [9] and multimodal addressing of recommendations indicates the potential to adopt the text and visual sources of information to imbue the personalisation more expressive and explicable [8].




Figure 2 – Dynamic User–Context Modeling Pipeline

This is particularly important in cognizing semantics by consumers that are not directly amenable to expressing preferences using suggestive notation, but rather express these through natural language queries, keywords, description or content queries/interactions. By employing learning with keyword, more discriminative expression of interest by the users of the domain-oriented recommendation systems can be achieved [11]. CAPF then brings together math semantic embeddings as well as feature presentations that allow the mechanism to correlate the contextual situations with sensible user preferences as opposed to relying on numerically interacting backgrounds separately.

3.4 Adaptive Recommendation Intelligence Layer

An adaptive recommendation layer is used to implement the core intelligence of CAPF. This layer is fed with the current user-context representation where the recommendation of the candidates of the services or service action is obtained. Among them, one can assume a combination of a unique range of strategies of recommendation and they are: collaborative filtering, content-based learning, sequence modeling, deep neural networks, contextual rankings and hybrid recommendations.

The process of recommendation takes into consideration long-term and short-term interests. The long-term preferences aid in achieving stability, and the short-term behavior aids in altering immediately. These time dimensions have been demonstrated helpful in joint modelling applied in making personalized e-commerce recommendation [7]. CAPF works on this concept and goes further with it through supplementing information of a current situation to come up with the final ranking of recommendation.

Explainable outputs can be also supported by the recommendation layer. In addition to shown ranked items, this framework is capable of matching recommendations with situational or preference characteristics e.g. the most recent trends of interaction, specified interests or semantic similarity. Explainability enhances transparency and it might help users to find out why certain services or content are chosen.

3.5 Feedback-Driven Optimization Layer

Personalization This is a continuous process as opposed to a single prediction process. The system would be tracking key user responses such as choice, refused, time consumed, enhanced remarks, repeated or dropped activities, choice and abandonment of activities once recommended or given the service. These reactions are transformed to feed forward and fed in the optimization layer.




Figure 3 – Adaptive Recommendation and Feedback Loop

Optimization component observes the behavior of the suggestions and is applied to revise user representations and rank the parameters and personalization policies on each person. An illustration of one of them is in reinforcement-learning-based recommendation wherein the user response can be taken into account in its development of a subsequent set of decisions [10]. CAPF also proclaims this rule to other digital services through providing feedback to keep making additional improvements to the further suggestions.

The changing tastes are also determined through feedback loop. To give an example, a category that lies outside and to which we have been paying little attention, may be made to be more relevant, and a category that lies outside and against which we have always been taking the cold shoulder, may become less relevant. So the framework can change as time goes by without necessarily having to create the profile of the user completely.

3.6 Service Optimization and Decision Layer

CAPF extends on top of special service optimization layer of ranking recommendations. This layer will select the best response service which will depend on the situation that has been customized and outcome of the recommendation system. This output may be as recommended products, based on application, as education content, healthcare content, entertainment content, travel suggestions or dynamically selected digital content.

Relevance, Diversity, Freshness, User satisfaction, Latency, Business requirements and service availability are some of the objectives that may be added to the decision machine/system. This transforms personalization into more of a decision-optimization rather than problem-selection of an item. The architecture is thus able to accommodate various application specific policies and retain the identical pipeline of personalization.

3.7 Privacy, Governance, and Trust Layer

CAPF does not consider privacy and governance as a post-processing move. The structure provides access control to vulnerable user information, restricts access data, consent, anonymization or pseudonymization, implementing policy, and audits. Federated recommendation Strategies show how bespoke redesigns can be cultivated, lessen reliance on a centrally gathered information [12].




Figure 4 – Privacy-Aware Personalization Architecture

The governance layer also encourages model transparency, responsible data use, model explainability, as well as tracking personalization decisions. Where feasible, an increasing amount of the processing of data can be done nearer to the origin of the data and only the required or needed representations/model changes get sent back to the centralized components. This type of architecture will enable CAPF to provide a balance between performance and privacy as well as regulatory demands of personalization.

3.8 Continuous Personalization Control Loop

The last architecture parameter of CAPF is that it has a continuous control loop. The Introduction of context cues in the system is based on the acquisition layer, cues are converted to dynamic user-context representations which is further enriched by semantic processing and multicomponent processing and delivered to the recommendation and optimization of service layers. This is then accompanied by taking of user response as feedback and then using feedback to modify personalization options at a later stage.

This architecture defines a series of signal to context to preference to recommendation to service action to feedback to adaptation. These stages are dissociable allowing the single parts to evolve independently and then the entire system does not have the need to be redesigned. It can also enable CAPF to serve an assortment of machine-learning models, information streams, and domains of use, as well as environments.

In general, CAPF brings together capabilities that have been previously studied independently, like temporal preference modelling [1], AI-based recommendation [2], dynamically evolving intent recognition [3], preference dynamics [4], adaptive customization of preferences [5], dynamic representation learning [6] and long and short-term interest dynamism [7], model explaining [8], multi-feature learning [9], reinforced adaptations [10], semantically characterization of preferences [11] and privacy-conscious recommendation [12]. With an integrated set of these services into a single context-sensitive platform, CAPF offers a base of scalable, flexible, explainable and privacy-responsible personalization of heterogeneous digital services.

IV. EMPIRICAL VALIDATION AND ADAPTIVE PERFORMANCE ASSESSMENT

The proposed Context-Aware Personalization Framework (CAPF) team needs to be looked at in terms of not only classic measures of recommendation value, but on the capability to adapt with regard to the context changes, to compensate to the user feedback and hold the services accountable. The review therefore looks at a wide range of factors cutting in on the effect of suggestions, context fit, computational efficiency, clarifiable and privacy.

4.1 Recommendation Effectiveness

The ability of CAPF to produce some customized recommendations, which can be used, is evaluated in the first dimension of evaluation. They could be applied in typical recommendation metrics Precision at K, Recall at K, F1-



score, Normalized Discounted Cumulative Gain (NDCG) and Mean Reciprocal Rank (MRR). CAPF is similar to the conventional collaborative filtering, content recommendation, and implicit user-profile. This should be specifically looked at in terms of whether contextual and temporal information would enhance the ranking quality as compared to non-contextual baselines. The fact that long-term and short-term preferences are combined is likely to enhance relevance as user preferences fluctuate in a short time frame [1], [7].

4.2 Contextual Adaptation

Contextual responsiveness takes into consideration the functionality of the framework to responds to changes in user conditions and intent immediately. Control variations of temporal conditions, session behavior, device usage or contextual preference can be induced, through experiments and time and accuracy with which CAPF updates recommendations. Such methods offer conceptual foundations of application used in this evaluation, i.e. dynamic intent modelling and preference-evolution techniques [3], [4]. A good structure should only serve to reduce errors which are involved when using old profiles to give recommendations and be consistent in situations where the conditions of the context are not changing.

4.3 Feedback and Personalization Gain

A measure of improvement of the recommendations when used by the user with the next user can be used to evaluate the feedback-driven component. It is possible to trace easy steps like cumulative reward, click-through rate, acceptance rate, satisfaction score/ prediction errors alternative, as far as consecutive interaction is concerned. It goes to determine how CAPF can be enhanced as the accumulated feedback goes on. To assess this adaptive ability a good analogy would be the reinforcement-learning-based recommendation [10]. Improvements on the interaction cycles would be an indication of personalization as a constant learning mechanism and not a predictive mechanism.

4.4 Scalability and Computational Performance

CAPF must react to or measure with growing user counts, events occurring, items and simultaneous number of requests as well. Major indicators are response latency, throughput, memory consumption, model-update time and computational overhead. By comparing experiments between centrally and distributed realizations of the scheme it is possible to conclude whether the architecture can scale to be capable of supporting a big-scale digital platform. This idea of federated recommendation and resource-efficient can be applied to consider the scalability and distributed personalization [12].

4.5 Explainability, Privacy, and Overall Utility

It should also conduct qualitative and quantitative evaluation to determine how well the explanations and privacy are upheld. Explainability can be measured in terms of relevance of recommendation rationales, consistency and legibility of rationales, and most especially, textual cues or visual cues and contextual cues are relevant in a decision [8], [9]. Examples of privacy considerations include the minimum data, local processing, access control and sensitive user information of the user. Lastly, CAPF might be obtained together with a composite perception of utility consisting of relevance, variety, responsiveness, latency, clarification and confidentiality. The accuracy does not give a more realistic evaluation of an intelligent personalization architecture compared to such multidimensional evaluation.

Typically, the evaluation strategy should demonstrate that CAPF can be effective in enhancing the relatability of the recommendations in real-time, responding to various situations, learning through feedback, and being scaled to large numbers of users and maintaining trusted personalization. This type of multiple-dimensional analysis helps to understand that the aim of the framework of transforming recommendation into an adaptive digital-service improvement capacity is much more than a simple problem of ranking.

V. CONCLUSION AND FUTURE RESEARCH DIRECTIONS

5.1 Conclusion

One of the significant features of intelligent digital platforms is contextual personalization since requirements of the users and services demands are continuously changing as they arise on the basis of behavior, time, semantics and environment contexts. In the current paper a framework of the Context-Aware Personalization Framework (CAPF) has been provided as one concept of intelligent recommendation and optimization of the digital services. The fact that other traditional recommendation ideas tend to emphasize user-item engagement forecasting has transformed CAPF because it views personalization as a dynamic end-to-end process that involves the context acquisition process, user active model, semantically-defined inclination, adaptive recommendation process, feedback-involved optimization, and a privacy-sensitive ruling.



This model is a mixture of fixed user features and information which changes dynamically in an attempt to be more dynamically responsive personalized. The ease of presenting heterogeneous information to the decision to recommend and the feedback-based optimization layer, both supported by its semantic and multi-modal representation enablers, makes sure that the information regarding user feedbacks is constantly realigned. The architecture is also intrinsically designed with regard to explainability and privacy and is not designed to be discrete post processing functions. The suggested evaluation framework also lays the groundwork of a multidimensional approach to evaluate the effectiveness of a recommendation based on contextual responsiveness and adaptation, scalability, explainability, and privacy.

On the whole, there is a comprehensive architectural perspective of CAPF that interrelates the works on the time-based recommendation, dynamical intent modelling, adaptive preference learning, multimodal representation, reinforcement-guided recommendation, and privacy conscious personalisation. The main value addition it has made is uniting these capabilities in a shared framework that is capable of handling various digital-service environments.

5.2 Future Work

CAPF can be expanded in a number of directions in future research. To test the validity of the framework to actual world scenarios; First, one can test the functionality of the framework under large-scale scenarios by applying behavioral and contextual streams generated constantly to test the functionality of the framework. Second, engaging in the development of advanced generative AI and large language models can be involved to enhance semantic user modeling, conversational recommendation, and explain generators. Third, it can also be applied to multimodal context fusion which can be to more elaborate combinations of text, visual, behavioral or environmental cues.

Future studies are also necessary with the aim of having privacy saving personalization based on the federated learning, secure computation and decentralized model optimization. It is possible to explore adaptive fairness mechanisms to detect and prevent possible biases in customized judgments. Lastly, it is also possible to study the self-directed personalization agents in future research investigations to dynamically choose models, maximize the recommendation policy and it can also be optimized to come up with a variety of goals, e.g. relevance, diversity, latency, privacy and user satisfaction. These extensions have the potential to introduce enhancements to CAPF and facilitate scalability as a plausible, scalable and intelligent backbone to digital-service eco systems.

REFERENCES

- [1] J. Zhang et al., “TLSAN: Time-aware long- and short-term attention network for next-item recommendation,” *Neurocomputing*, 2021.
- [2] N. Bheemisetty, “AI-powered recommendation systems: Best practices and real-world applications,” *International Journal of Future Innovative Science and Technology (IJFIST)*, vol. 7, no. 6, p. 13926, 2024.
- [3] X. Zhang et al., “Dynamic intent-aware iterative denoising network for session-based recommendation,” *Information Processing & Management*, 2022.
- [4] A. Pujahari et al., “Modeling users’ preference changes in recommender systems via time-dependent Markov random fields,” *Expert Systems with Applications*, 2023.
- [5] Z. Liu et al., “Dual-view preference learning for adaptive recommendation,” *IEEE Transactions on Knowledge and Data Engineering*, 2023.
- [6] T. Liu et al., “Dynamic and static representation learning network for recommendation,” *IEEE Transactions on Neural Networks and Learning Systems*, 2024.
- [7] Y. Xiao et al., “A joint learning recommendation model for E-commerce platforms integrating long-term and short-term interests,” *IEEE Transactions on Services Computing*, 2024.
- [8] P. Liu et al., “Dynamic attention-based explainable recommendation with textual and visual fusion,” *Information Processing & Management*, 2020.
- [9] X. Gu et al., “Sequence neural network for recommendation with multi-feature fusion,” *Expert Systems with Applications*, 2022.
- [10] L. Liu et al., “An interactive food recommendation system using reinforcement learning,” *Expert Systems with Applications*, 2024.
- [11] L. Chen et al., “Keywords-enhanced contrastive learning model for travel recommendation,” *Information Processing & Management*, 2024.
- [12] M. Imran et al., “ReFRS: Resource-efficient federated recommender system for dynamic and diversified user preferences,” *ACM Transactions on Information Systems*, 2023.